



GRADEABILITY

STANDARD EQUIPMENT


- Proportional controls
- Automatic pothole protection
- Self-closing gate on platform
- Drivable at full height
- Non-marking tyres
- 2WD
- Automatic brake system
- Emergency lowering system
- Emergency stop button
- Cylinder holding valve
- Onboard diagnostic system
- Tilt sensor with alarm
- All motion alarm
- Horn
- Hour meter
- Forklift pockets
- Charger protection
- Flashing beacon
- Overload sensor with alarm
- Extended platform

OPTIONS:

- AC power to the platform
- Platform work lights
- Airline to platform

Rizer

SELF-PROPELLED VERTICAL LIFTS (SINGLE MAST RAM STEER)



POTHOLE DEVICE



TIGHT TURNING
RADIUS RAM
STEERING



FORKLIFT POCKETS



EMERGENCY
LOWERING SYSTEM



- S.W.L
MAX. OCCUPANTS
- WORKING HEIGHT
PLATFORM FLOOR HEIGHT
- OVERALL LENGTH
OVERALL WIDTH
OVERALL HEIGHT
PLATFORM SIZE (LENGTH/WIDTH)
PLATFORM EXTENSION SIZE
GROUND CLEARANCE (STOWED)
GROUND CLEARANCE (RAISED)
WHEELBASE
TURNING RADIUS (INSIDE/OUTSIDE)
- DRIVE MOTORS
LIFTING MOTOR
- TRAVEL SPEED
Stowed
Raised
Up/Down speed
- BATTERIES
INTEGRATED CHARGER
- GRADEABILITY
MAXIMUM SLOPE
- TYRES
- WEIGHT
Standard platform
With extend platform

MV060-RS

- 150kg
- 1
- 8.00m
- 6.00m
- 1.41m
- 0.76m
- 1.99m
- 0.78x0.70m
- 0.55m
- 0.05m
- 0.019m
- 1.07m
- 0/1 .55m
- 2x24VDC/0.5kW
- 24VDC/2kW
- 4km/h
- 1.1km/h
- 24/25sec
- 2x12V/85Ah
- 24V/11A
- 25%
- 1.5°/3°
- Ø305x100mm
- 1060kg
- 1102kg

MV075-RS

- 125kg
- 1
- 9.50m
- 7.50m
- 1.41m
- 0.76m
- 1.99m
- 0.78x0.70m
- 0.55m
- 0.05m
- 0.019m
- 1.07m
- 0/1 .55m
- 2x24VDC/0.5kW
- 24VDC/2kW
- 4km/h
- 1.1 km/h
- 31/24sec
- 2x12V/85Ah
- 24V/11A
- 25%
- 1.5°/3°
- Ø305x100mm
- 1120kg
- 1162kg

