



E-Tech
























SELF-PROPELLED SCISSOR LIFTS (AC ELECTRIC DRIVE)

STANDARD FEATURES

- + Brushless AC drive system
- + Proportional controls
- + Automatic pothole protection
- + Self-closing gate on platform
- + Drivable at full height
- + Non-marking tyres
- + 2WD
- + Automatic brake system
- + Emergency lowering system
- + Onboard diagnostic system
- + Tilt sensor with alarm
- + All motion alarm
- + Forklift pockets
- + Folding handrails
- + Extended platform
- + Charger protection
- + Flashing beacon
- + Overload sensor with alarm

OPTIONAL OVERHEAD WARNING SYSTEM AVAILABLE



	S0808-ACE	S0812-ACE	S1012-ACE	S1212-ACE	S1412-ACE
 S.W.L	230kg	450kg	320kg	320kg	250kg
 S.W.L ON EXTENSION	113kg	113kg	113kg	113kg	113kg
MAX. OCCUPANTS - INDOOR	2	2	2	2	2
MAX. OCCUPANTS - OUTDOOR	0	2	1	0	0
 WORKING HEIGHT	10.00m	10.00m	12.00m	13.80m	15.70m
 PLATFORM FLOOR HEIGHT	8.00m	8.00m	10.00m	11.80m	13.70m
 OVERALL LENGTH	2.48m	2.48m	2.48m	2.48m	2.84m
 OVERALL WIDTH	0.83m	1.15m	1.15m	1.19m	1.25m
OVERALL HEIGHT - RAILS UP	2.36m	2.36m	2.49m	2.62m	2.62m
OVERALL HEIGHT - RAILS DOWN	2.0m	1.83m	1.96m	2.09m	2.09m
PLATFORM SIZE	2.27x0.81m	2.27x1.12m	2.27x1.12m	2.27x1.12m	2.64x1.12m
PLATFORM EXTENSION SIZE	0.90m	0.90m	0.90m	0.90m	0.90m
GROUND CLEARANCE - STOWED	0.019m	0.019m	0.019m	0.019m	0.019m
GROUND CLEARANCE - RAISED	0.10m	0.10m	0.10m	0.10m	0.10m
WHEELBASE	1.87m	1.87m	1.87m	1.87m	2.22m
TURNING RADIUS - INSIDE	0m	0m	0m	0m	0m
TURNING RADIUS - OUTSIDE	2.10m	2.20m	2.20m	2.20m	2.65m
 GRADEABILITY	25%	25%	25%	25%	25%
 MAXIMUM SLOPE	1.5°/3°	1.5°/3°	1.5°/3°	1.5°/3°	1.5°/3°
STOWED SPEED	5.0km/h	5.0km/h	5.0km/h	5.0km/h	5.0km/h
 RAISED SPEED	0.8km/h	0.8km/h	0.8km/h	0.8km/h	0.8km/h
 UP/DOWN SPEED	32/36sec	26/33sec	42/45sec	46/40sec	63/71sec
 DRIVE MOTOR	2x24VAC/.87kW	2x24VAC/.87kW	2x24VAC/.87kW	2x24VAC/.87W	2x24V/.87kW
 LIFTING MOTOR	24VAC/3.5kW	24VAC/3.5kW	24VAC/3.5kW	24VAC/3.5kW	24VAC/3.5kW
 BATTERIES	24V/170Ah	24V/170Ah	24V/220Ah	24V/220Ah	24V/220Ah
 INTEGRATED CHARGER	24V/30A	24V/30A	24V/30A	24V/30A	24V/30A
 TYRES	Ø381x127mm	Ø381x127mm	Ø381x127mm	Ø381x127mm	Ø381x127mm
 WEIGHT	2230kg	2710kg	3060kg	2990kg	3360kg



CONTACT

+64 (021) 361 599 | Clint Norgrove, National Sales Manager
 0800 4 LIFTX (0800) 454 389
 Office: +64 (03) 348 0750
www.liftx.co.nz